

GYROSCOPIC MIXER

BIAX | 35

»The Workhorse«

Classic robustness

- | Facade paints
- | Plasters
- | Dispersions
- | Varnishes



PRODUCT
VIDEO



Proven

»Classic« loading concept. Robust technology, particularly beneficial for heavy containers, proven 10,000 times over in practice.

Sturdy

Very smooth-running in combination with a maximum number of revolutions even with high mixing loads.

Durable

Maximum reliability over many years. Even with heavy loads.

MADE IN

GERMANY

Features

- Extremely smooth-running, even with large and heavy containers.
- Reliable mixing unit, proven 10,000 times worldwide.
- Space-saving, two-part sliding door; single-handed operation.
- Particularly kind to containers due to gyroscopic mixing of viscous materials.
- Reduction in service costs as all the components are easy to access.

GYROSCOPIC
MIXER

BIAX
35

Technical data

CONTAINER	
Max. mixing weight	40 kg
Rec. continuous working weight	35 kg
Container height	70 – 400 mm
Max. container diameter	365 mm
Container type	round / oval / metal / plastic
Multiple containers at the same time	yes (only with closed protective ring)
PERFORMANCE	
Power supply	230 V/50 Hz (110 V/60 Hz optional)
Motor output	1.1 kW
Max. speed	160 rpm (programmable)
Rec. mixed throughput	high
OPERATION	
Mixing times	3 programmable times
Door option	manual sliding door
Loading type	manual extractable clamping plate
Clamping plate / loading height	445 mm (+20 mm)
Can be combined with roller conveyor	no
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	777 x 820 x 1110 mm
Machine weight	209 kg
Shipping dimensions (W x D x H)	800 x 1200 x 1300 mm
Shipping weight	231 kg
Transport rollers	yes
Installation	adjustable 4-foot installation



Collomix GmbH

Daimlerstraße 9
85080 Gaimersheim
Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.com