



GYROSCOPIC MIXER TORO | neo

»The expert
for small PoS«

smartCONNECT
READY

PRODUCT
VIDEO



- | Dispersion
- | Facade paints
- | Plasters
- | Wood protection

Reliable

No downtime caused by dirty drive, clamping elements and electronics caused by paint spills thanks to the unique splash protection.

Ease of use

Collomix's Push and Slide loading concept makes it effortless to load the machine. The ease of use reduces the physical strain of operating any heavy paint.

Fast

Optimized workflow for speed. Manual fixation of the handle using rubber bands is eliminated and the handle is automatically secured by the built-in handle restraints.

MADE IN

GERMANY

 **Collomix**
.colorTEC



Features

- Intelligent Auto-Mix feature can automatically choose mixing time by either pressing one button or simply by closing the door.
- Splash Guard prevents mixer downtime by protecting clamping and rotation mechanism of paint pollution.
- Built-in handle restraint for fast loading and to avoid rattling noise during operation.
- Low noise emission and smooth operation at Point-of-Sale.
- Easy handling and loading – even of heavy paint-containers due to wide loading board.
- Onboard accelerometer measures vibration and can optionally adjust the mixing parameters in real-time.
- Door can be easily swapped from left to right-handed opening.
- All electronics are contained in one single module which can be replaced or upgraded in less than a minute.
- Optional smartCONNECT gives you access to realtime data on usage and performance.

Technical data

CONTAINER	
Max. mixing weight	40 kg
Rec. continuous working weight	30 kg
Container height	60 - 400 mm
Max. container diameter	360 mm
Container type	round, oval, metal, plastic
PERFORMANCE	
Power supply	230 V / 50 Hz (opt. 110 V / 60 Hz)
Motor output	1.1 KW
Max. speed	145 rpm (programmable, variable)
Rec. mixing throughput	low to medium
Multiple can mixing	yes
OPERATION	
Mixing times	3 programmable times
Clamping pressure & mixing speed	automatic - depending on 3 selectable containers hights
Door option	manual swing door (door opening left or right)
Loading type	Push & Slide incl. wide loading board
Clamping plate / loading height	385 mm (± 10 mm)
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	782 x 811 x 1007 mm
Machine weight	152 kg
Shipping dimensions (W x D x H)	800 x 900 x 1270 mm
Shipping weight	168 kg
Transport rollers	yes
Installation	adjustable 4-foot installation
SERVICE	
Splash guard index	large splash protection



Collomix GmbH

Daimlerstraße 9

85080 Gaimersheim

Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.com