



PREMIUM SHAKER VIBA X.30

»The 3rd generation!
Our best
PoS expert«

Made to last!
Most silent shaker in the industry

- | Varnishes
- | Dispersions
- | many other liquids

smartCONNECT
READY

PRODUCT
VIDEO



Silent

Quietest shaker in the market due to full acoustic analysis, precision manufacturing and exact tolerances.

Install & Forget

Designed to last and be reliable – no matter what happens at PoS – Automatic door and clamping mechanics are protected against paint spills. Service calls reduced to a minimum thanks to best “Collomix” durability.

Fast & smartMIX

Short and effective mixing times. Highest throughput at PoS. Best ergonomics thanks to self-opening integral door and smartMIX (single button operation, intuitive mixing intelligence and intelligent clamping control ICC).

MADE IN

GERMANY

 **Collomix**
.colorTEC

VIBA | X.30

Low throughput

Medium throughput

High throughput

Very high throughput



Features

- Intelligent Clamping Control (ICC) reduces paint spills to a minimum – unique in the market.
- Integral door design for optimal space-saving at PoS.
- Auto-Open-Door-Function and roller at loading board for fast and easy loading.
- Spindle cover for optimal protection and handle fixation.
- Low noise emission at PoS, since particularly smooth-running and low-vibration.
- Convenient installation using transport rollers and adjustment-free 3-foot installation.

| **VIBA X.30 V:** Unrivalled flexibility when using a wide range of containers and materials due to individually configurable mixing frequencies.

Technical data



CONTAINER	VIBA X.30	VIBA X.30 V
Max. mixing weight	40 kg	40 kg
Rec. continuous working weight	30 kg	30 kg
Container height	50 - 400 mm	50 - 400 mm
Mixing plate dimensions	370 x 360 mm	370 x 360 mm
Top clamping plate dimensions	350 x 360 mm	350 x 360 mm
Container type	round / oval / metal / plastic	round / oval / metal / plastic
Multiple containers at the same time	yes	yes
PERFORMANCE		
Power supply	230 V / 50 Hz	230-240 V / 50-60 Hz
Motor output	0.9 kW	0.9 kW / frequency converter
Variable speed	no	Up to 6 speed intervals per mixing program
Recommended mixed throughput	medium to high	medium to high
OPERATION		
Mixing times	3 programmable times	3 mixing programmes
Clamping pressure	automatic - depending on 3 selectable containers heights	automatic - depending on 3 selectable containers heights
Door option	automatic integral door	automatic integral door
Loading type	Push & Slide incl. loading board	Push & Slide incl. loading board
Loading board height	497 mm (+ 30 mm)	497 mm (+ 30 mm)
Can be combined with roller conveyor	yes	yes
SHIPPING AND INSTALLATION		
Machine dimensions (W x D x H)	735 x 590 x 1208 mm	735 x 590 x 1208 mm
Machine weight	130 kg	131 kg
Shipping dimensions (W x D x H)	800 x 630 x 1300 mm	800 x 630 x 1300 mm
Shipping weight	146 kg	147 kg
Transport rollers	yes	yes
Installation	adjustment-free 3-foot installation	adjustment-free 3-foot installation
SERVICE		
Splash guard index	Spindle cover	Spindle cover



Collomix GmbH

Daimlerstraße 9
85080 Gaimersheim
Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.com